

ADDERView[®] CCS-MV 4224 Multi-Viewer

Command and control multi-viewer switch for sharing 4K video, keyboard and mouse, plus audio between four computers.

Features

Video performance

Up to UHD 4K video output resolution is generated, thus providing a crystal clear display, even with a quad window layout.

Automatic switching

Free-Flow KVM and audio control between ports without the need to press any buttons. Simply move the mouse between windows.

Flexible screen layout

Use preset window layouts, or move and resize windows to create custom layouts. Dual output ports allow for extended or duplicated displays.

Channel identification

Reduce the chances of operator error by displaying a meaningful name for each channel. The port LED and window border colors may also be configured.

USB performance

Emulated USB2.0 ports for fast switching of HID (Human Interface Devices), such as keyboard and mouse. Hi-speed USB3.0 switched port for mass storage and isochronous devices, including flash drives, headsets and web cams.

Flexible computer connections

Connect to a combination of single and dualhead computers.

Analog audio

Bi-directional analog audio. An audio 'Hold' facility assigns the audio connection to a specific computer whilst the KVM is switched to another computer. Useful when a user needs to talk to one channel, whilst working on another.

Digital audio mixer

Option to combine audio signal from multiple HDMI[®] channels. Adjust the volume level for each channel.

Copy & Paste

Copy text between Windows 10 computers using standard keyboard, Ctrl+C and Ctrl+V commands.

Remote control

Select layout presets and input channels remotely for control room applications where the displays are used to aid situation awareness.

Matrix integration

The ADDERView® CCS Multi-Viewer (CCS-MV) may be connected to the ADDERLink® INFINITY matrix system. This allows the user to control any 4 computers connected to the matrix network.

Product in Brief

The ADDERView® CCS Multi-Viewer (CCS-MV) provides simultaneous, real-time KVMA (Keyboard, Video, Mouse and Audio) access of up to four computers from a single workstation. Users can instantly take control of the target computer by simply moving the mouse between windows, providing the experience of a single desktop.

- Manage both single and dual-head 4K computers
- Display a configurable channel name on the front panel display to aid identification
- No software installation is required for the target computers (apart from Windows dual-head computers)





Technical Specifications

Video resolutions

• The system supports video resolutions up to UHD 4K (3840x2160 @30Hz) at 4:4:4 with 8 bits per color

Software compatibility

• Windows, Linux, Mac host computer OS's

Console connections

 2x digital ports for HDMI®, 2x USB 2.0 full speed Type A, 4x USB3.0 Hi-speed Type A. Audio 3.5mm/0.13" jack for microphone and headphones, RJ12 serial port

Computer connections

 4x dual ports for DisplayPort[™]/HDMI[®], 4x USB2.0 full speed Type B, 4x USB 3.0 Hispeed Type B, Audio 3.5mm line in and out

Front Panel

 Audio hold button and status LED, 4x
Channel selection button and status LED, 212x104 E-paper status display

Physical design

- Robust metal construction
- 344mm/13.54"(W) x 44mm/1.73"(H) x 161mm/6.34"(D)
- Weight: 1.6kg/3.53lbs

Power supply

- 100-240V AC, 47/63Hz
- 12V DC 30W output from power supply unit

Environmental

- Operating temperature: 0°C to 40°C/32°F to 104°F
- Storage temperature: -20° to 60°C/-4° to 140°F
- Humidity: 0-80% RH, non-condensing

Approvals

• UKCA, CE, FCC class A, TUV US & Canada



ADDERView CCS-MV 4224 - Front



ADDERView CCS-MV 4224 - Rear

Ordering Information

CCS-MV4224: ADDERView CCS Multi-Viewer 4-port 4K switch

What's in the Box?

1x CCS-MV 4K switch1x Power supply unit with mains cable1x Quick start guide

Accessories (Sold separately)

RMK13: Rackmount kit VSCD18: 2m/6.5ft DisplayPort[™] video cable VSCD15: 2m/6.5ft HDMI[®] video cable VSC22: 2m/6.5ft Audio cable VSC24: 2m/6.5ft USB cable Type A to Type B

About Adder

Adder is a leading developer and thought leader in connectivity solutions. Adder's advanced range of KVM switches, extenders and IP solutions enable the control of local, remote and global IT systems across the enterprise. The company distributes its products in more than 60 countries through a network of distributors, resellers and OEMs.

Adder has offices in China, Germany, Japan, the Netherlands, Singapore, Spain, France, Sweden, United Kingdom and United States.

To find out more, visit: adder.com

Global Headquarters Tel: +44 (0)1954 780044 | Fax: +44 (0)1954 78008 Email: sales@adder.com

Americas Tel: +1 888 932 3337 | Fax: + **Asia Pacific** 275 1117 Tel: +65 628

Asia Pacific Tel: +65 6288 5767 | Fax: +65 6284 115

All brand names and trademarks are the property of their respective owner. Copyright 2020 | Adder Technology Ltd. | ADDER_DS093_EN_v3_FINAL Infomation contained in this data sheet is up-to-date and correct as the date of issues. As Adder Technology cannot control or anticipate the conditions under which this product may be used each use should revi the infomation in the specific context of planed use. Images are for illustrative guraness ends.

