

# VT-PDU 4PS Switched PDU



- Switched per outlet
- Managed Power Distribution Unit



## Specifications

CPU Speed / RAM / OS	2 cores, 720mHz / 128Mb / Linux v.6.2
Ethernet	10/100Mbps
Outlets	Switched per outlet manually or using logic. x4 IEC C13 outlets, 110-240V AC, 50/60 Hz.
Inlet	IEC C14 inlet, 110-240V AC, 50/60Hz, Fuse 10A
Reserve power	12V DC terminal for PCB power reservation
USB Type-C	For USB camera, USB flash, USB hub
CAN port	Connect up to x32 sensors & extensions
LAN	Ethernet 10/100 Base-T port
SD memory slot	Up to 512 Gb SDHC
Mounting	Wall, 19", or Vertical bar (purchased separately)
Warranty	3 years
Support	Online portal



## Supports

- Centralized Monitoring & Control**
  - Responsive Web Interface
  - SNMP v1, v2c, v3
- Scalability**
  - CAN sensor and extensions
  - Modbus TCP/IP, 4-20mA, 0-10V,
- Improved security**
  - OpenVPN, SSL, HTTPS
  - Three-tier data access permissions with login
- Protocol support**
  - DHCP, HTTP, HTTPS, DynDNS, SMTP, RADIUS,
  - Syslog, NTP server, HTTP request
- API**
  - XML, JSON
- System Usability**
  - Multi-language mobile interface
  - First-time wizard
  - Sensor & outlet parameters graphing
- Virtual sensors / devices / elements**
  - PING, Timers, Triggers, Logic schemes, SNMP GET, IP cameras, Groups, Math
- Notifications and alerts**
  - E-mail, SMS, Phone dial, SNMP Traps, Web-to-SMS, SMS link
- Logging**
  - SD card, USB flash, E-mail, FTP